

The **mětrix** package

Tobias Weh*

Version 1.3 – Released 2016/03/21

Abstract

— — — — — | — ˘ ˘ — ˘ ˘ —
et quod temptabam | scribere versus erat

The **mětrix** package can be used to print the prosodics/metrics of (latin) verses. It provides macros to typeset the symbols stand alone and in combination with syllables (including automatic alignment like seen above). Furthermore it defines a new br̄vis and a lōnga accent¹ and a bow to contract syllables.

Thanks to David Carlisle, Marco Daniel, Enrico Gregorio, Bruno Le Floch and Joseph Wright who helped me with starting in LATEX3 programming. The verse above is by Ovid in his Tristia 4,10,26.

1 Prerequisites

mětrix relies only on a few packages: tikz (including the calc library), xpatch and xparse, which stand for the whole LATEX3 bundle.

2 Package loading

Load **mětrix** as usual with \usepackage{metrix}. At the moment it has no options.

A CWL file metrix.cwl for autocompletion in TeXstudio is available in the GitHub repo. To install the CWL file copy it to ~/.config/texstudio/ on Linux and OS X and to C:\Documents and Settings\User\AppData\Roaming\texstudio/. See section 1.5 of the TeXstudio manual for more information.

*URL: <http://tobiw.de/en>, Mail: mail@tobiw.de

¹I know that these signs are no accents in the liguistic sense, but they are in the TeX tradition ...

3 Bugs and feedback

3.1 Known issues

- At the moment the escaping of hyphen chars is not that good (see section 7.3).
- Unfortunatly you can't use the active quotes of `csquotes` inside of `\metrics` syllable list (see section 7.4).

I'm sure there are more bugs and issues let me know if you find them ...

3.2 Feedback

Any feedback on `mētrix` is appreciated. You may use its GitHub repository at <https://github.com/tweh/mētrix> to request features and report bugs or send me an e-mail (mail@tobiw.de).

Please note that I don't speak latin myself and forthat the examples in this manual may be wrong—as long as they show how to use the package I don't consider such errors as bugs ;-).

4 Metric symbols

4.1 Syntax for symbols

Before I'll show you the central macros for typesetting the symbols, you need to “learn” the syntax for the symbols. All symbols are represented by a single or a combination of characters. The list with all available abbreviations can be found in table 1. Please keep in mind that `mētrix` uses spaces to separate the abbreviations an something like `_ 'x` will cause an error, the correct input is `_ ' x`.

4.2 Stand alone metric symbols

`\metricsymbols *` `\metricsymbols{(*) [⟨highlighting⟩]}{⟨symbols⟩}`

This macro typesets stand alone versions of the symbols, i.e. without syllables below (or above) of them. Use the starred version for smaller (in line) symbols and the normal version for bigger symbols. `⟨symbols⟩` must be a list of abbreviations as explained in section 4.1; the abbreviations must be separated by one (or more) spaces.

Example

The *diphilius* can be shown with this code.

```
\metricsymbols{_ _uu _ _uu u_ | x _ u u _ x u_}  
— oo — oo ü | x — ü ü — x ü
```

Table 1: Symbol abbreviations

| abbreviation | symbol | explantion |
|---------------------------------|--------|---------------------------|
| e | | empty (=invisible) symbol |
| u | ˘ | elementum breve |
| _ <i>under score</i> | — | elementum longum |
| uu | ˘˘ | double breve |
| uu_ | ˘˘ | elementum biceps |
| _uu | ˘˘ | elementum biceps |
| u_uu | ˘˘ | elementum anceps |
| x | × | elementum anceps |
| n | ˘ | elementum indifferens |
| u_ | ˘ | elementum indifferens |
| oo <i>two lowercase o's</i> | ○○ | aeolic base |
| <i>pipe</i> | | break (see 4.4) |
| <i>two pipes</i> | | verse break (see 4.4) |
| ' <i>apostrophe (shift + #)</i> | | shorter break (see 4.4) |
| , <i>comma</i> | | shorter break (see 4.4) |

4.3 Metric symbols above (or below) syllables

`\metrics *` `\metrics[<highlighting>]{<symbols>}f{<syllables>}`

This command can be used to align the symbols above (or below) syllables. The first argument works as in `\metricsymbols`, the second argument `<syllables>` takes the hyphenated verse.

Example

```
\metrics{_ u u _ _ _ | _ _ u u _ _ _ }  
{flos ve-te-ri-s vi-ni | meis na-ri-bus ob-iec-tust}  
  
— ~ ~ — — | — — ~ — —  
flos veteris vini | meis naribus obiectust
```

You may use multiple spaces to align the abbreviations above the syllables but this is not mandatory and does not affect the output. But mind that the number of syllables equals the number of symbols. If you use the `oo` symbol you may omit the hyphen between the two syllables belonging to this symbol. You can merge multiple words by *embracing* them.

Example

```
\metrics{_ u u _ _ _ }  
{mol-ta quo-{que et} bel-lo pas-sus}  
  
— ~ ~ — — —  
molta quoque et bello passus
```

The macros `\metrics` and `\metricsymbols` can also be used to typeset single symbols or symbol syllable combinations.

Example

The `\metricsymbols*{_uu}` shows an `\emph{elementum biceps}`.
The `oo` shows an *elementum biceps*.

4.4 Adding symbols for breaks

As seen in the examples above you can use pipes, i.e. `|` or `||`, to mark breaks. In `\metrics` the markers must appear in `<symbols>` and `<syllables>`.

Example

```
\metrics{_ u u _ _ _ | _ _ u u _ ||}  
{flos ve-te-ri-s vi-ni | meis na-ri-bus ob ||}
```

$\overline{\text{flos}} \quad \overset{\circ}{\text{o}} \overset{\circ}{\text{o}} - \overset{-}{\text{--}} | \overset{-}{\text{--}} \overset{\circ}{\text{o}} \overset{\circ}{\text{o}} \overset{-}{\text{--}} \parallel$

If you want the breaks to be shown in the symbol line only you can use the shorter break which is represented by an apostrophe (shift + #) or a comma. This mark must be used in $\langle symbols \rangle$ only and is kind of special:

- It *can't* be highlighted and thus doesn't count for the numbers used for highlights,
- it is ignored at the beginning and the end of $\langle symbols \rangle$,
- in `\metricsymbols` it is treated like the pipe, and
- TeX needs at least one additional run to get the right positions.

Example

```
\metrics{_ u u ' _ u u ' _ _ ' _ _ | _ u u | _ _ ||}
        {Ar-ma vi-rum-que ca-no Troiae qui | pri-mus ab | o-ris ||}

_ ^ ^ | - ^ ^ | - - | - | - - | - ^ ^ | - - ||
```

Arma virumque cano Troiae qui | primus ab | oris ||

The difference between ' and , is that the break defined with an apostrophe is vertically centred between the surrounding symbols while the break set with the comma is vertically centred between the corresponding syllables. They both align horizontally within the row of symbols.

Example



```
\emph{apostrophe:}
\metrics{_ - , }
        {au-ra-{r\bow{um e}st}} \qquad
\emph{comma:}
\metrics{_ - , }
        {au-ra-{r\bow{um e}st}}
apostrophe: aurarum est      comma: aurarum est
```

4.5 Highlight certain symbols/syllables

As you can see above `\metrics` and `\metricsymbols` got an optional argument taking some options to highlight a certain symbol/syllable. The $\langle highlighting \rangle$ list must contain one or more comma separated pairs of $\langle numbers \rangle = \langle style \rangle$, where $\langle numbers \rangle$ is the number of a symbol/syllable (e.g. 3) or a list of numbers separated by plus signs (e.g. 2+3+5) in the list and $\langle style \rangle$ is any TikZ style (other TikZ options may not work properly, so you maybe must create your own style, see section 7.9.)

mětrix comes with several predefined highlighting styles:

- **add arrow**

This style adds an arrow above the metric symbol. To change the arrow symbol, edit the variable `metrix`.

- **add text=(text)**



This style takes a *mandatory* argument to add some text above a symbol. To change the default font change the font of the TikZ node style `every metrix added text`.

- **bold highlight**



- **colored highlight=(color)**



This style has an *optional* argument to change the highlighting color on the fly. To change the color in general change the value of the variable `highlightcolor`.

- **dashed highlight**



- **filled highlight=(color)**



This style has an *optional* argument to change the filling color on the fly. To change the color in general change the value of the variable `fillcolor`.

- **superscript=(text)**



This style takes a *mandatory* argument to add a superscript letter or a number to a symbol. It is designed to work with the break symbols, but works with others too.

Styles with an argument must be set in braces (see the examples)!

Example

Highlight some syllables with color.

```
\metrics
```

```

[  

  2=colored highlight,  

  4={colored highlight=orange},  

  5={colored highlight=blue},  

  7=colored highlight,  

  11=colored highlight  

]  

{_ u u _ _ _ | _ _ u u _ }  

{flos ve-te-ris vi-ni | meis na-ri-bus ob}  

— ^ ^ — — | — — ^ ^ —  

flos veteris vini | meis naribus ob

```

Example

The shorter version using the + syntax.

```

\metrics[2+5+9=bold highlight]  

{_ u u _ _ _ | _ _ u u _ }  

{flos ve-te-ris vi-ni | meis na-ri-bus ob}  

— ^ ^ — — | — — ^ ^ —  

flos veteris vini | meis naribus ob

```

Example

Mixing and combining styles is possible too.

```

\metricsymbols[1+4=bold highlight, 3=colored highlight]  

{u_uu x _ || u _ n ||} \\  

\metricsymbols[2={bold highlight,colored highlight}]  

{u_uu x _ || u _ n ||}  

\S\S x — || ^ — ⌂ ||  

\S\S x — || ^ — ⌂ ||

```

Example

Add some superscripts to the breaks.

```

\metricsymbols[6={superscript=5},10={colored highlight,superscript=bD}]  

{_ _uu _ _uu _ | _uu _ _uu || _ uu _ u_}  

— \S\S — \S\S — |^5 \S\S — \S\S ||^bD — \S\S — \S\S

```

5 Accents and bows

\brv * \brv{\langle vowel \rangle} \lng{\langle vowel \rangle} \acct{\langle vowel \rangle}

\lng * The first commands offer an alternative to the standard accent macros \u and \=. The difference is that \brv centers the accent above the vowel or diphthong and \lng stretches the bar across the whole vowel or diphthong. \acct adds an accent dot below a vowel or diphthong.²

Example

Add accents to all vowels.

```
\brv{a}m\acct{\lng{i}}c\brv{u}s pr\acct{\brv{o}}f\brv{u}g\brv{u}s  
ămīčus prőfugus
```

mětrix also tries to do some kind of italic correction, and shifts the accents a little to the right when an italic or slanted font is used.

| | | | | | |
|-------|-------|----------|-------|-------|----------|
| ü ü ü | í í í | æ æ æ | ü ü ü | í í í | æ æ æ |
| ú ú ú | í í í | ææ ææ ææ | ú ú ú | í í í | ææ ææ ææ |
| ụ ụ ụ | ị ị ị | ae ae ae | ụ ụ ụ | ị ị ị | ae ae ae |

Fine Tuning

To make some fine tuning for a certain accent possible the three macros actually got some additional, *optional* arguments:

```
\brv(<coordinate>){<vowel>}  
\lng(<coordinate>) [<left length>] {<vowel>} [<right length>]  
\acct(<coordinate>){<vowel>}
```

Where *<coordinate>* must be a valid TikZ coordinate and can be used to move the accent. In addition to that the accent produced by \lng can be extended with *<left/right length>* by a certain amount.

Example

Prevent collision between accent and descender of an f.

```
\itshape somn\acct(-0.05em,-0.45ex){i}fero  
somnifero
```

²Actually you can use any vowel, diphthong, syllable or word as *<vowel>*, it makes no difference as long as it is text.

```
\bow *
```

```
\bow{\langle syllables \rangle}
```

\bow can be used to show the contraction of two vowels or syllables.

Example

```
mult\bow{um i}lle or d\bow{ei}nde
```

```
multum ille or deinde
```

Fine Tuning

To make some fine tuning for a certain bow possible the macro actually has some additional, *optional* arguments:

```
\bow(\langle coordinate \rangle) [⟨left length⟩] {⟨syllable⟩} [⟨right length⟩]
```

Where ⟨left/right length⟩ can be used to shorten the bow by a certain amount.

Example

Prevent collision between accent and bow.

```
c\acct{oe}-1\bow{um \acct{e}}[2pt]st
```

```
coe-lum est
```

6 Environments

```
symbolline
```

This environment can be used to display a line of stand alone symbols.

Example

```
Text text text ...
\begin{symbolline}
  \metricsymbols{oo e _ u u _ e u _ e u _ u_}
\end{symbolline}
Text text text ...

Text text text ...
```

OO — ∟ ∟ — ∟ — ∟ — ∟ — ∟ —

```
Text text text ...
```

metricverses

```
\begin{metricverses}{\langle source \rangle}
  \langle content optional \verseref{\langle reference \rangle} \rangle
\end{metricverses}
```

Use this environment to display a verse with metric symbols, separate multiple verses by a blank line.

Example

```
Text text text ...
\begin{metricverses}
  \metrics{_ u u _ _ _ | _ _ _ u u _ _ _ }
    {flos ve-te-riſ vi-ni | meis na-ri-bus ob-iec-tust}

  \metrics{_ u u _ u u _ | _ _ _ - u u
            _ u u _ }
    {ei-us a-mor cu-pi-dam | {\m\bowl{e h}uc} pro-li-cit
      per te-ne-bras}
\end{metricverses}
Text text text ...

Text text text ...

$$\begin{array}{c|ccccc} \text{flos} & \text{veteris} & \text{vini} & \text{meis} & \text{naribus} \\ \text{ei} & \text{us} & \text{a} & \text{mor} & \text{cu} \\ \text{pro} & \text{li} & \text{ci} & \text{t} & \text{per} \\ \text{te} & \text{ne} & \text{bras} & & \end{array}$$

Text text text ...
```

verseref

```
\verseref{\langle reference \rangle}
```

Inside of `{metricverses}` you may use `\verseref` to print a reference.

Example

```
Text text text ...
\begin{metricverses}
  \metrics{_ u u _ _ _ | _ _ _ u u _ _ _ }
    {flos ve-te-riſ vi-ni | meis na-ri-bus ob-iec-tust}
  \verseref{Plaut. \emph{Curc.} 96f}

  \metrics{_ u u _ u u _ | _ _ _ - u u
            _ u u _ }
    {ei-us a-mor cu-pi-dam | {\m\bowl{e h}uc} pro-li-cit
      per te-ne-bras}
\end{metricverses}
Text text text ...
```

Text text text ...

flos veteris vini | meis naribus obiectust
eius amor cupidam | mehuc prolicit per tenebras

Plaut. *Curc.* 96f

Text text text ...

7 FAQs

7.1 How can I display the symbols below the syllables?

Change the variable symbolshift to a negative value.

Example

```
\setmetrixvar{symbolshift}{-0.6em}
% later ...
\metrics{_ u u _ _ _ | _ _ _ u u _ _ _ }
{flos ve-te-ris vi-ni | meis na-ri-bus ob-iec-tust}

flos veteris vini | meis naribus obiectust
```

7.2 How can I combine two words below one symbol?

Use braces {} in the lists to keep them processed as one element.

Example

```
\metrics{u u _ _ | _ _ u u }
{cu-pi-dam | {m\bowl{e h}uc} pro-li-cit }

cupidam | mehuc prolicit
```

7.3 How can I show a hyphen character?

To escape a hyphen - put it inside braces, but you must still add an unbraced hyphen to show **métrix** where your syllables split.

Example

If you enclose the hyphen in braces together with a syllable, the symbol gets centered above both.

```
\metrics{_ _ _ }
{vi{-ni} }

vi-ni
```

You can enclose only the hyphen in braces and treat it as a syllable but then you must add an empty symbol e too.

```
\metrics{_ e _}
{vi-{-}-ni}
vi-ni
```

7.4 How can I use quotes in \metrics?

It should be possible to use all shorthands (or direct input with Unicode) etc. for quotation marks except the active quotes of csquotes, which won't work inside the \metrics syllable list. It is possible to use csquotes besides **mětrix** though.

Example

```
\metrics{ _ u }{ "si me" }
\metrics{ _ u }{ \glqq si me\grqq }% with \usepackage[<lang>]{babel}
\metrics{ _ u }{ "si me" }% with \usepackage[ngerman]{babel}
"si me" „si me“ „si me“
```

7.5 How can I add a superscript letter to a certain symbol?

Use the superscript highlighting style as described above.

7.6 How can I make subscripts instead of superscripts?

The easiest way is to use the superscript style and change a part of its definition to shift the superscripts to subscript positions.

Example

```
\metricsymbols[2={superscript=x}]{ u || u } \qquad vs. \qquad \qquad
%
\tikzset{
    every superscript picture/.style={
        baseline=1ex,
    },
}
%
\metricsymbols[2={superscript=x}]{ u || u }
\qquad \qquad \qquad vs. \qquad \qquad \qquad \qquad
```

Normally the \tikzset should be part of your preamble, I used it this way to show the differences.

7.7 How can I highlight all symbols/syllables?

Way 1 Just call your desired highlighting style before using on of the macros \metrics or \metricsymbols. You may enclose this in a group to not affect the other following sequences. Mind that the highlighting styles must be in a way changing the every ... styles to make this way work.

Example

```
{% begin group
    \tikzset{colored highlight}
    \metrics{_ u u _ _ _ }
        {flos ve-te-riſ vi-ni}
}%
} end group
— ^ ^ — —
flos veteris vini
```

Way 2 Change the every metrix ... styles.

Example

```
{% begin group
    \tikzset{every metrix symbol/.append style={red}}
    \metrics{_ u u _ _ _ }
        {flos ve-te-riſ vi-ni}
}%
} end group
— ^ ^ — —
flos veteris vini
```

Leave out the grouping (and put this to your preamble) if you want to highlight the symbols in your whole document.

7.8 How can I change the size of a symbol?

Change the two base vector units.

Example

```
\setmetrixvar{baseunit}{1em}
\setmetrixvar{bigbaseunit}{1.6em}
```

If you want to change the size of a single symbol to highlight it you must create your own highlighting style.

Example

```
\tikzset{
    bigger highlight/.style={
        every metrix symbol/.append style={x=2.5em,y=2.5em,line width=1.5pt},
    },
}
% later
\metricsymbols[2=bigger highlight]{u_uu x _ || u _ n x}

\textcolor{brown}{\textcolor{brown}{X}} — \| \textcolor{brown}{\textcolor{brown}{u}} — \textcolor{brown}{\textcolor{brown}{n}} x
```

7.9 How can I stop highlighting the syllables too?

Way 1 Change the highlight styles (in your preamble).

Example

```
\tikzset{
    colored highlight/.style={
        every metrix symbol/.append style={
            draw=\usemetrixvar{highlightcolor},
        },
    },
}
% later ...
\metrics[3=colored highlight]{_ u u _ _ _ }
                           {flos ve-te-ris vi-ni}

— \textcolor{brown}{\textcolor{brown}{u}} — —
flos veteris vini
```

Way 2 Create your own highlighting style, which is very similar to way 1, as the following example shows. Every own style should change the appearance by appending the settings to one of the `every ...` styles.

Example

```
\tikzset{
    my highlight/.style={
        every metrix symbol/.append style={draw=blue,line width=0.07em},
```

```

        }
    }
\metrics[5=my highlight]{{_ u u _ _ _ }{flos ve-te-ris vi-ni}
    _ ^ ^ _ _ —
flos veteris vini

```

7.10 Why got the highlight styles that long names?

To prevent conflict with other packages.

Example

If you want to shorten it create your own style as described above or use

```
\tikzset{
  hl/.style={colored highlight}
}
```

to map the style to a shorter name. Then you can use it like in

```
\metricsymbols[2=hl]{u _ _ u}
```

7.11 How can I change the font of all syllables?

Extend the `every metrix syllable node` style

Example

Print all syllables in italic with the following extension.

```
\tikzset{
  every metrix syllable node/.append style={font=\itshape},
}
```

8 Customization

Some hints were already given in the FAQ section (see section 7) but here I will list all variables and TikZ styles that are in use and can be changed to customize **m̄etrix** easily.

8.1 Variables

`\setmetrixvar` `\setmetrixvar{\langle variable \rangle}{\langle value \rangle}`

`\usemetrixvar`

To customize the rendering of the symbols, accents and bow **m̄etrix** has some variables that you can change. Use `\setmetrixvar` to change a value. The variables and the default values are listed in table 2. To access a value you can use `\usemetrixvar{\langle variable \rangle}`.

It is highly recommended to use font size depending units, i.e. `em` or `ex`, for all lengthen to keep the symbols usable in different font sizes, for example in headlines or footnotes.

Example

Change the highlighting color to blue.

```
\setmetrixvar{highlightcolor}{blue}
% later
\metrics[5=colored highlight]{_ u u _ _ _ }
                           {flos ve-te-ri-s vi-ni}
— ^ ^ — —
flos veteris vini
```

Example

Create your own highlighting style but use the default highlighting color.

```
\tikzset{
    my highlight/.style={
        every metrix symbol/.append style={
            draw=\usemetrixvar{highlightcolor},
            line width=0.15em
        },
    },
}
\metrics[5=my highlight]{_ u u _ _ _ }
                           {flos ve-te-ri-s vi-ni}
— ^ ^ — —
flos veteris vini
```

Table 2: Variables

| variable | default | explanation |
|----------------------------------|---------------------|--|
| <code>symbol linewidth</code> | <code>0.04em</code> | line width of symbols above syllables and small stand alone symbols |
| <code>bigsymbol linewidth</code> | <code>0.06em</code> | line width of big stand alone symbols |
| <code>accent linewidth</code> | <code>0.03em</code> | line width of accents (<code>\l ng</code> and <code>\b rv</code>) |
| <code>bow linewidth</code> | <code>0.03em</code> | line width of bows (<code>\bow</code>) |
| <code>symbol sep</code> | <code>0.4em</code> | gap between symbols in stand alone lists |
| <code>base unit</code> | <code>0.9em</code> | length of the base vector for drawing symbols above syllables, small stand alone symbols, accents and bows |
| | | ... |

Table 2: Variables (cont.)

| variable | default | explanation |
|----------------------------|----------------|--|
| bigbaseunit | 1.4em | length of the base vector for drawing stand alone symbols |
| shortsyllablelimit | 0.8em | all syllables shorter than this can be treated specially, e.g. they'll get a shorter elementum longum. |
| gap | 0.09em | small gap between lines of the symbols, e.g. the distance between the two lines of a verse break |
| symbolshift | 1.1em | length to shift the symbols above or below the syllables (try -0.6em to display the symbols below the base line) |
| l _{ng} shift | 0.8em | length to shift the longa accent |
| l _{ng} shortening | 0.075em | length to shorten the longa accent a little |
| l _{ng} minlength | 0.25em | minimum width of a longa accent |
| b _{rv} shift | 0.9em | length to shift the brevis accent |
| dotshift | -0.15em | length to shift the dot accent |
| i _t correction | 0.11em | length to shift the accents above italic/slanted letters |
| accentxshift | -0.025em | length to shift the accents horizontally |
| bowshift | -0.15em | length to shift the bow below the base line |
| bowshortening | 0.15em | length to shrink the bow a little |
| bowlooseness | 0.75 | value to influence the bending of the bow |
| symbolcolor | black | color of metric symbols |
| accentcolor | black | color of accents (\l _{ng} and \b _{rv}) |
| bowcolor | black | color of bows (\bow) |
| highlightcolor | red | color of highlighted symbols and syllables used in colored highlight style |
| fillcolor | yellow | color of filled symbol nodes used in filled highlight style |
| arrow | \$\downarrow\$ | arrow for highlighting |
| breakgap | 0.6em | gap before and after a (verse) break |
| emptywidth | 1em | gap replacing an empty symbol (abbreviation e) |

8.2 TikZ styles

Beside the variables you may change the TikZ styles used by **mětrix**. But please mind that all styles are not empty by default so you should prefer `/append style` against `/style`. Otherwise it may cause strange effects. Remind that you can use `\usemetrixvar` to access a variable.

`every metrix symbol`
`every metrix big symbol`
`every metrix symbol node`

These three styles define the appearance of the metric symbols. They define the line width, the color, the basis vectors and other things.

`every metrix syllable node`
`every metrix break node`

These styles defines the nodes in which a syllable or a break symbol (the ones spanning across the symbol and the syllable line) is typeset, e.g. it aligns these nodes at their base line.

`every metrix accent`

This style defines the appearance of accents created by `\lng` and `\brv`.

`every metrix bow`

This style defines the appearance of bows below symbols.

`bold highlight`
`colored highlight`
`dashed highlight`
`filled highlight`
`superscript`

These styles can be used to highlight a certain symbol.

`every superscript picture`
`every superscript node`
`every superscript label`

These styles are used to define the superscript highlighting style.

`every metrix added text`

This style is used for text added to a symbol with the `add text` highlighting.

9 Implementation

```
1  {*package}
2  (@@=metrix)
3  \ProvidesExplPackage
4    {\metrixFileName}{\metrixFileDate}{\metrixFileVersion}{\metrixFileDescription}
```

9.1 Required packages

```
5  \RequirePackage{xparse}
6  \RequirePackage{xpatch}
7  \RequirePackage{tikz}
8  \ExplSyntaxOff
9  \usetikzlibrary{calc}
10 \ExplSyntaxOn
```

9.2 Variables

All variables are internal. The user can change them via `\setmetrixvar` and use them via `\usemetrixvar`.

`\g_metrix_variable_symbollinewidth_tl` This variable stores the line width for all metric symbols above (or below) syllables.

```
11 \tl_new:N \g_metrix_variable_symbollinewidth_tl
12 \tl_set:Nn \g_metrix_variable_symbollinewidth_tl { 0.04em }
(End definition for \g_metrix_variable_symbollinewidth_tl.)
```

`\g_metrix_variable_bigsymbollinewidth_tl` This variable stores the line width for all stand alone metric symbols.

```
13 \tl_new:N \g_metrix_variable_bigsymbollinewidth_tl
14 \tl_set:Nn \g_metrix_variable_bigsymbollinewidth_tl { 0.06em }
(End definition for \g_metrix_variable_bigsymbollinewidth_tl.)
```

`\g_metrix_variable_accentlinewidth_tl` This variable stores the line width of the accent like symbols.

```
15 \tl_new:N \g_metrix_variable_accentlinewidth_tl
16 \tl_set:Nn \g_metrix_variable_accentlinewidth_tl { 0.04em }
(End definition for \g_metrix_variable_accentlinewidth_tl.)
```

`\g_metrix_variable_bowlinewidth_tl` This variable stores the line width of the bow.

```
17 \tl_new:N \g_metrix_variable_bowlinewidth_tl
18 \tl_set:Nn \g_metrix_variable_bowlinewidth_tl { 0.04em }
(End definition for \g_metrix_variable_bowlinewidth_tl.)
```

`\g_metrix_variable_symbolsep_tl` This variable stores the gap between two or more stand alone metric symbols.

```
19 \tl_new:N \g_metrix_variable_symbolsep_tl
20 \tl_set:Nn \g_metrix_variable_symbolsep_tl { 0.4em }
(End definition for \g_metrix_variable_symbolsep_tl.)
```

`\g_metrix_variable_baseunit_tl` This variable stores the length of the basis vector for all metric symbols above (or below) syllables and accent like symbols.

```
21 \tl_new:N \g_metrix_variable_baseunit_tl
22 \tl_set:Nn \g_metrix_variable_baseunit_tl { 0.9em }
(End definition for \g_metrix_variable_baseunit_tl.)
```

\g__metrix_variable_bigbaseunit_t1 This variable stores the length of the basis vector for all stand alone metric symbols.

```
23 \tl_new:N \g__metrix_variable_bigbaseunit_t1  
24 \tl_set:Nn \g__metrix_variable_bigbaseunit_t1 { 1.4em }
```

(End definition for \g__metrix_variable_bigbaseunit_t1.)

\g__metrix_variable_gap_t1 Length for small gaps in the symbols, e.g. the gap between the two bows of an elementum biceps.

```
25 \tl_new:N \g__metrix_variable_gap_t1  
26 \tl_set:Nn \g__metrix_variable_gap_t1 { 0.09em }
```

(End definition for \g__metrix_variable_gap_t1.)

\g__metrix_variable_symbolshift_t1 This variable stores the value to shift metric symbols above (or below) syllables. Set this variable to approx 1.1em to draw the symbols above the syllable and to -0.6em to draw them below.

```
27 \tl_new:N \g__metrix_variable_symbolshift_t1  
28 \tl_set:Nn \g__metrix_variable_symbolshift_t1 { 1.1em }
```

(End definition for \g__metrix_variable_symbolshift_t1.)

\g__metrix_variable_lngshift_t1 This variable stores the value to shift the longa accent.

```
29 \tl_new:N \g__metrix_variable_lngshift_t1  
30 \tl_set:Nn \g__metrix_variable_lngshift_t1 { 0.15em }
```

(End definition for \g__metrix_variable_lngshift_t1.)

\g__metrix_variable_lngshortening_t1 This variable stores the value to shorten the longa accent.

```
31 \tl_new:N \g__metrix_variable_lngshortening_t1  
32 \tl_set:Nn \g__metrix_variable_lngshortening_t1 { 0.075em }
```

(End definition for \g__metrix_variable_lngshortening_t1.)

\g__metrix_variable_lngminlength_t1 This variable stores the value to shorten the longa accent.

```
33 \tl_new:N \g__metrix_variable_lngminlength_t1  
34 \tl_set:Nn \g__metrix_variable_lngminlength_t1 { 0.25em }
```

(End definition for \g__metrix_variable_lngminlength_t1.)

\g__metrix_variable_brvshift_t1 This variable stores the value to shift the brevis accent.

```
35 \tl_new:N \g__metrix_variable_brvshift_t1  
36 \tl_set:Nn \g__metrix_variable_brvshift_t1 { 0.25em }
```

(End definition for \g__metrix_variable_brvshift_t1.)

\g__metrix_variable_dotshift_t1 This variable stores the value to shift the brevis accent.

```
37 \tl_new:N \g__metrix_variable_dotshift_t1  
38 \tl_set:Nn \g__metrix_variable_dotshift_t1 { -0.15em }
```

(End definition for \g__metrix_variable_dotshift_t1.)

| | |
|---|--|
| <code>\g__metrix_variable_itcorrection_tl</code> | These variables are used to set the italic correction of accents. |
| <code>\l__metrix_internal_itcorrection_tl</code> | |
| <code>\g__metrix_internal_itcorrection_zero_tl</code> | |
| | <pre>39 \tl_new:N \g__metrix_variable_itcorrection_tl 40 \tl_set:Nn \g__metrix_variable_itcorrection_tl { 0.11em } 41 \tl_new:N \l__metrix_internal_itcorrection_tl 42 \tl_set:Nn \l__metrix_internal_itcorrection_tl { 0em } 43 \tl_new:N \g__metrix_internal_itcorrection_zero_tl 44 \tl_set:Nn \g__metrix_internal_itcorrection_zero_tl { 0em }</pre> |
| | <i>(End definition for \g__metrix_variable_itcorrection_tl, \l__metrix_internal_itcorrection_tl, and \g__metrix_internal_itcorrection_zero_tl.)</i> |
| <code>\g__metrix_variable_accentxshift_tl</code> | This variable is used to shift the accents horizontally. |
| | <pre>45 \tl_new:N \g__metrix_variable_accentxshift_tl 46 \tl_set:Nn \g__metrix_variable_accentxshift_tl { -0.025em }</pre> |
| | <i>(End definition for \g__metrix_variable_accentxshift_tl.)</i> |
| <code>\g__metrix_variable_bowshift_tl</code> | This variable stores the value to shift the bow. |
| | <pre>47 \tl_new:N \g__metrix_variable_bowshift_tl 48 \tl_set:Nn \g__metrix_variable_bowshift_tl { -0.15em }</pre> |
| | <i>(End definition for \g__metrix_variable_bowshift_tl.)</i> |
| <code>\g__metrix_variable_bowshortening_tl</code> | This variable stores the value to shrink the bow. |
| | <pre>49 \tl_new:N \g__metrix_variable_bowshortening_tl 50 \tl_set:Nn \g__metrix_variable_bowshortening_tl { 0.15em }</pre> |
| | <i>(End definition for \g__metrix_variable_bowshortening_tl.)</i> |
| <code>\g__metrix_variable_bowlowness_tl</code> | This variable stores the value to shrink the bow. |
| | <pre>51 \tl_new:N \g__metrix_variable_bowlowness_tl 52 \tl_set:Nn \g__metrix_variable_bowlowness_tl { 0.75 }</pre> |
| | <i>(End definition for \g__metrix_variable_bowlowness_tl.)</i> |
| <code>\g__metrix_variable_symbolcolor_tl</code> | These variables store the color of symbols, accents and bows. |
| <code>\g__metrix_variableAccentcolor_tl</code> | |
| <code>\g__metrix_variable_bowcolor_tl</code> | |
| | <pre>53 \tl_new:N \g__metrix_variable_symbolcolor_tl 54 \tl_set:Nn \g__metrix_variable_symbolcolor_tl { black } 55 \tl_new:N \g__metrix_variable Accentcolor_tl 56 \tl_set:Nn \g__metrix_variable Accentcolor_tl { black } 57 \tl_new:N \g__metrix_variable_bowcolor_tl 58 \tl_set:Nn \g__metrix_variable_bowcolor_tl { black }</pre> |
| | <i>(End definition for \g__metrix_variable_symbolcolor_tl, \g__metrix_variableAccentcolor_tl, and \g__metrix_variable_bowcolor_tl.)</i> |
| <code>\g__metrix_variable_highlightcolor_tl</code> | These variable stores the color used in the colored <code>highlight</code> style. |
| | <pre>59 \tl_new:N \g__metrix_variable_highlightcolor_tl 60 \tl_set:Nn \g__metrix_variable_highlightcolor_tl { red }</pre> |
| | <i>(End definition for \g__metrix_variable_highlightcolor_tl.)</i> |

\g__metrix_variable_fillcolor_tl These variable stores the color used in the filled highlight style.

```
61 \tl_new:N \g__metrix_variable_fillcolor_tl  
62 \tl_set:Nn \g__metrix_variable_fillcolor_tl { yellow }  
  
(End definition for \g__metrix_variable_fillcolor_tl.)
```

\g__metrix_variable_arrow_tl These variable stores the color used in the filled highlight style.

```
63 \tl_new:N \g__metrix_variable_arrow_tl  
64 \tl_set:Nn \g__metrix_variable_arrow_tl { $\downarrow$ }  
  
(End definition for \g__metrix_variable_arrow_tl.)
```

\g__metrix_variable_breakgap_tl This variable stores the width of the gap around the two break symbols.

```
65 \tl_new:N \g__metrix_variable_breakgap_tl  
66 \tl_set:Nn \g__metrix_variable_breakgap_tl { 0.6em }  
  
(End definition for \g__metrix_variable_breakgap_tl.)
```

\g__metrix_variable_emptywidth_tl This variable stores the width of the gap caused by an empty symbol (abbreviation e).

```
67 \tl_new:N \g__metrix_variable_emptywidth_tl  
68 \tl_set:Nn \g__metrix_variable_emptywidth_tl { 1em }  
  
(End definition for \g__metrix_variable_emptywidth_tl.)
```

\l__metrix_words_tl This list stores the words of the \metrics macro.

```
69 \tl_new:N \l__metrix_words_tl  
  
(End definition for \l__metrix_words_tl.)
```

\l__metrix_syllables_seq This list stores the words of the \l__metrix_words_tl list.

```
70 \seq_new:N \l__metrix_syllables_seq  
  
(End definition for \l__metrix_syllables_seq.)
```

\l__metrix_symbols_seq This list stores the metric symbols of \metrics and \metricsymbols.

```
71 \seq_new:N \l__metrix_symbols_seq  
  
(End definition for \l__metrix_symbols_seq.)
```

\l__metrix_short_breaks_seq This list stores the short and foot breaks of \metrics.

```
72 \seq_new:N \l__metrix_short_breaks_seq  
73 \seq_new:N \l__metrix_foot_breaks_seq  
  
(End definition for \l__metrix_short_breaks_seq and \l__metrix_foot_breaks_seq.)
```

\l__metrix_highlights_prop This list stores the highlighting styles of \metrics and \metricsymbols.

```
74 \prop_new:N \l__metrix_highlights_prop  
  
(End definition for \l__metrix_highlights_prop.)
```

| | |
|---|---|
| <code>\l__metrix_highlight_seq</code> | This lists are used to evaluate a higlight style. |
| <code>\l__metrix_highlight_pos_seq</code> | <pre> 75 \seq_new:N \l__metrix_highlight_seq 76 \seq_new:N \l__metrix_highlight_pos_seq </pre> <p>(End definition for <code>\l__metrix_highlight_seq</code> and <code>\l__metrix_highlight_pos_seq</code>.)</p> |
| <code>\q__metrix_space_marker</code> | <p>This is the marker for spaces inside of the <code>\l__metrix_words_tl</code> list.</p> <pre> 77 \quark_new:N \q__metrix_space_marker </pre> <p>(End definition for <code>\q__metrix_space_marker</code>.)</p> |
| <code>\l__metrix_process_int</code> | <p>This process counter is used to combine the symbols and syllables.</p> <pre> 78 \int_new:N \l__metrix_process_int </pre> <p>(End definition for <code>\l__metrix_process_int</code>.)</p> |
| <code>\l__metrix_short_syllable_bool</code> <code>\l__metrix_syllable_box</code> <code>\g__metrix_variable_shortsyllablelimit_tl</code> | <p>This boolean can be used to store that a syllable is short, e.g. <i>li</i> will be defined as short wheras <i>man</i> is long. That will be used to shorten the <code> _ </code> symbol. Furthermore we'll need a box to measure the length of a syllable and a variable to save the limit for short syllables.</p> <pre> 79 \bool_new:N \l__metrix_short_syllable_bool 80 \box_new:N \l__metrix_syllable_box 81 \tl_new:N \g__metrix_variable_shortsyllablelimit_tl 82 \tl_set:Nn \g__metrix_variable_shortsyllablelimit_tl { 0.8em } </pre> <p>(End definition for <code>\l__metrix_short_syllable_bool</code>, <code>\l__metrix_syllable_box</code>, and <code>\g__metrix_variable_shortsyllablelimit_tl</code>.)</p> |

9.3 Variants

Later we'll need the following variant.

```

83 \cs_generate_variant:Nn \prop_item:Nn { No , Nf , NV , Nx }
84 \cs_generate_variant:Nn \prop_put:Nnn { Nnx , Nxx , Nff , Noo }
85 \cs_generate_variant:Nn \seq_item:Nn { Nf , NV , Nx }
86 \cs_generate_variant:Nn \seq_set_split:Nnn { Nnf , NnV , Nnx }

```

9.4 Internal main macros

| | |
|-----------------------------------|---|
| <code>__metrix_metrics:nn</code> | <p>This macro processes the two lists of <code>\metrics</code> and combines the symbols and syllables.³</p> <pre> 87 \cs_new_protected:Npn __metrix_metrics:nn #1 #2 88 { 89 \tl_set:Nx \l__metrix_words_tl { \tl_trim_spaces:n { #2 } } </pre> <p>First replace the spaces by a special marker <code>\q__metrix_space_marker</code> and add hyphens: a space becomes a syllable.</p> <pre> 90 \tl_replace_all:Nnn \l__metrix_words_tl { ~ } { - \q__metrix_space_marker - } </pre> |
|-----------------------------------|---|

³The framing of this macro was provided by Enrico Gregorio at <http://tex.stackexchange.com/q/124528/4918>, a follow up question was <http://tex.stackexchange.com/q/124698/4918>. David Carlisle and Bruno Le Floch lead me to the implementation of the highlighting mechanism, see <http://tex.stackexchange.com/q/124782/4918>

Then split the word list at hypens.

```
91 \seq_set_split:NnV \l__metrix_syllables_seq { - } \l__metrix_words_t1
```

Split the symbol list at spaces.

```
92 \seq_set_split:Nnx \l__metrix_symbols_seq { ~ } { \tl_trim_spaces:n { #1 } }
```

Search for the short and foot breaks and remove them afterwards.

```
93 \int_zero:N \l__metrix_process_int
94 \seq_clear:N \l__metrix_short_breaks_seq
95 \seq_clear:N \l__metrix_foot_breaks_seq
96 \seq_map_inline:Nn \l__metrix_symbols_seq {
  \int_incr:N \l__metrix_process_int
  \tl_if_eq:nnT { ##1 } { ' } {
    \seq_put_right:Nx \l__metrix_short_breaks_seq { \int_use:N \l__metrix_process_int }
    \int_decr:N \l__metrix_process_int
  }
  \tl_if_eq:nnT { ##1 } { , } {
    \seq_put_right:Nx \l__metrix_foot_breaks_seq { \int_use:N \l__metrix_process_int }
    \int_decr:N \l__metrix_process_int
  }
}
\seq_remove_all:Nn \l__metrix_symbols_seq { , }
\seq_remove_all:Nn \l__metrix_symbols_seq { ' }
```

Test whether both lists got the same length:

```
109 \int_zero:N \l__metrix_process_int
110 \seq_map_inline:Nn \l__metrix_syllables_seq
111 {
  \tl_if_eq:nnT { ##1 } { \q__metrix_space_marker } {
    \int_incr:N \l__metrix_process_int
  }
115 \int_compare:nTF
116 {
  \seq_count:N \l__metrix_syllables_seq -
  \seq_count:N \l__metrix_symbols_seq = \l__metrix_process_int
119 }
120 {
```

continue with list processing, if the numbers are equal:

```
121 \int_zero:N \l__metrix_process_int
122 \seq_map_inline:Nn \l__metrix_syllables_seq
123 {
  \int_incr:N \l__metrix_process_int
  \tl_if_eq:nnTF { ##1 } { \q__metrix_space_marker } {
    {
```

If the syllable is a space the process counter must be decremented and a space is typeset.

```
127 \int_add:Nn \l__metrix_process_int { -1 }
128 \c_space_token
129 }
130 {
```

Finally typeset the syllable and it's symbol.

```

131      \str_case:nnF { ##1 }
132      {
133          { | }
134          {
135              \__metrix_break_node:n { \__metrix_l_break: }
136          }
137          { || }
138          {
139              \__metrix_break_node:n { \__metrix_ll_break: }
140          }
141      }
142      {
143          \__metrix_print_syllable:n { ##1 }
144      }
145  }
146 }
```

And add the short break symbols if necessary:

```

147 \seq_if_empty:NF \l__metrix_short_breaks_seq {
148     \seq_map_inline:Nn \l__metrix_short_breaks_seq {
149         \int_set:Nn \l_tmpa_int { ##1 - 1 }
150         \bool_if:nF {
151             \int_compare_p:n
152             { 0 = \l_tmpa_int }
153             ||
154             \int_compare_p:n
155             { \seq_count:N \l__metrix_symbols_seq = \l_tmpa_int }
156         }
157         \tikz [remember-picture, overlay] {
158             \node [every-metrix-symbol-node] at
159                 ($(\l__metrix_symbol_node_\int_use:N \l_tmpa_int.east) !
160                 0.5!(\l__metrix_symbol_node_##1.west)$)
161             { \__metrix_short_break: };
162         }
163     }
164 }
165 }
```

And add the foot break symbols if necessary:

```

166 \seq_if_empty:NF \l__metrix_foot_breaks_seq {
167     \seq_map_inline:Nn \l__metrix_foot_breaks_seq {
168         \int_set:Nn \l_tmpa_int { ##1 - 1 }
169         \bool_if:nF {
170             \int_compare_p:n
171             { 0 = \l_tmpa_int }
172             ||
173             \int_compare_p:n
174             { \seq_count:N \l__metrix_symbols_seq = \l_tmpa_int }
175         }
176 }
```

```

176   \tikz [remember-picture, overlay] {
177     \coordinate (l__metrix_tmp_coord) at
178       ($({l__metrix_syllable_node_\int_use:N}\l_tmpa_int.east) !
179         0.5!({l__metrix_syllable_node_##1.west})$);
180     \node [every-metrix-symbol-node] at
181       ($({l__metrix_symbol_node_\int_use:N}\l_tmpa_int.east) !
182         ({l__metrix_tmp_coord}!({l__metrix_symbol_node_##1.west})$)
183       { \__metrix_foot_break: };
184     }
185   }
186 }
187 }
188 }
```

Send an error, else.

```

189 {
190   \__metrix_error_msg:n
191   {
192     Numbers~of~symbols~(\seq_count:N \l__metrix_symbols_seq)~and~syllables~
193     (\int_eval:n
194     {
195       \seq_count:N \l__metrix_symbols_seq - \l__metrix_process_int
196     })
197     ~mismatch.
198   }
199 }
```

(End definition for `__metrix_metrics:nn`)

`__metrix_metricsymbols:n` This macro works like `__metrix_metrics` but is used to print stand alone metric symbols via `\metricsymbols`.

```

201 \cs_new_protected:Npn \__metrix_metricsymbols:n #1
202 {
203   \seq_set_split:Nnx \l__metrix_symbols_seq { ~ } { \tl_trim_spaces:n { #1 } }
204   \int_zero:N \l__metrix_process_int
205   \seq_map_inline:Nn \l__metrix_symbols_seq
206   {
207     \int_incr:N \l__metrix_process_int
208     \int_compare:nT { \l__metrix_process_int > 1 }
209     {
210       \hskip{\usemetrixvar{symbolsep}}
211     }
212   \str_case:nnF { ##1 }
213   {
214     { , }
215     {
216       \__metrix_break_gap:
217       \__metrix_align_symbol:n { \__metrix_l_bigmark: }
218       \__metrix_break_gap:
219     }
220   }
221 }
```

```

219     }
220 { ' }
221 {
222   \__metrix_break_gap:
223   \__metrix_align_symbol:n { \__metrix_l_bigmark: }
224   \__metrix_break_gap:
225 }
226 { | }
227 {
228   \__metrix_break_gap:
229   \__metrix_align_symbol:n { \__metrix_l_bigmark: }
230   \__metrix_break_gap:
231 }
232 { '' }
233 {
234   \__metrix_break_gap:
235   \__metrix_align_symbol:n { \__metrix_ll_bigmark: }
236   \__metrix_break_gap:
237 }
238 { || }
239 {
240   \__metrix_break_gap:
241   \__metrix_align_symbol:n { \__metrix_ll_bigmark: }
242   \__metrix_break_gap:
243 }
244 {
245   \__metrix_align_symbol:n { \__metrix_print_symbol: }
246 }
247 }
248 }
249 }

(End definition for \__metricsymbols:n)

```

__metrix_print_syllable:n This macro combines a single syllable and the corresponding metric symbol taken from the symbol list index with the process counter.

```

250 \cs_new_protected:Npn \__metrix_print_syllable:n #1
251 {
252   \group_begin:

```

Check whether the current syllable is short or long and set the corresponding bbol.

```

253   \hbox_set:Nn \l__metrix_syllable_box { #1 }
254   \dim_compare:nTF
255   { \box_wd:N \l__metrix_syllable_box < \g__metrix_variable_shortsyllablelimit_tl }
256   { \bool_set_true:N \l__metrix_short_syllable_bool }
257   { \bool_set_false:N \l__metrix_short_syllable_bool }

```

Set up the current highlight if it is defined

```

258   \cs_set:Npx \__metrix_current_highlight: {
259     \prop_item:NV \l__metrix_highlights_prop \l__metrix_process_int
260   }

```

```

261 \expandafter\tikzset\expandafter{\_metrix_current_highlight:}
Finally print the syllable and the symbol above. Use {pgfinterruptboundingbox} so
that the symbol doesn't takes space ad doesn't cause gaps between the syllables.
262 \hbox_set:Nn \l_tmpa_box { \_metrix_print_symbol: }
263 \begin{tikzpicture}
264 [
265   remember picture,
266   baseline=(l__metrix_syllable_node_\int_use:N \l__metrix_process_int.base),
267 ]
268 \node [every-metrix-syllable-node]
269   (l__metrix_syllable_node_\int_use:N \l__metrix_process_int)
270   { #1 };
271 \begin{pgfinterruptboundingbox}
272   \node [every-metrix-symbol-node]
273     (l__metrix_symbol_node_\int_use:N \l__metrix_process_int)
274     at ($
275       (l__metrix_syllable_node_\int_use:N \l__metrix_process_int.base)
276       +
277       (0,\usemetrixvar{symbolshift})
278       +
279       (\tl_use:N \l__metrix_internal_itcorrection_t1,0)
280     $)
281   { \box_use:N \l_tmpa_box };
282 \end{pgfinterruptboundingbox}
283 \end{tikzpicture}
284 \group_end:
285 }

```

(End definition for `_metrix_print_syllable:n`)

`_metrix_print_symbol:` This command selects the right symbol by it's abbreviation.

```

286 \cs_new_protected:Npn \_metrix_print_symbol:
287 {
288   \cs_if_exist_use:cF
289   {
290     \_metrix_\seq_item:Nn \l__metrix_symbols_seq
291     { \l__metrix_process_int }_mark:
292   }
293   {
294     \_metrix_error_msg:n
295     {
296       Unknown~symbol~abbreviation~'\seq_item:Nn
297       \l__metrix_symbols_seq { \l__metrix_process_int }'.
298     }
299   }
300 }

```

(End definition for `_metrix_print_symbol:..`)

9.5 Internal auxiliary macros

`__metrix_error_msg:n` An abbreviation to throw an error message.

```

301 \cs_new_protected:Npn \__metrix_error_msg:n #1
302 {
303     \PackageError{ \metrixFileName } { #1 }
304     {
305         Please~take~a~look~at~the~manual~or~send~an~email.
306     }
307 }
```

(End definition for `__metrix_error_msg:n`.)

`__metrix_warning_msg:n` An abbreviation to throw an error message.

```

308 \cs_new_protected:Npn \__metrix_warning_msg:n #1
309 {
310     \PackageWarning{ \metrixFileName } { #1 }
311 }
```

(End definition for `__metrix_warning_msg:n`.)

`__metrix_align_symbol:n` This macro aligns the metric symbols in a stand alone list.

```

312 \cs_new_protected:Npn \__metrix_align_symbol:n #1
313 {
314     \group_begin:
315     \cs_set:Npx \__metrix_current_highlight: {
316         \prop_item:NV \l__metrix_highlights_prop \l__metrix_process_int
317     }
318     \expandafter\tikzset\expandafter{\__metrix_current_highlight:}
319     \begin{tikzpicture}
320         [
321             baseline={(0,-0.25*\usemetrixvar{baseunit})},
322         ]
323         \node [every-metrix-symbol-node] {#1};
324     \end{tikzpicture}
325     \group_end:
326 }
```

(End definition for `__metrix_align_symbol:n`.)

`__metrix_break_gap:` This macro typesets the gap around the two break symbols.

```

327 \cs_new_protected:Npn \__metrix_break_gap:
328 {
329     \hspace{\usemetrixvar{breakgap}}
330 }
```

(End definition for `__metrix_break_gap:..`)

`__metrix_break_node:n` This macro typsets the gap around the two break symbols.

```
331   \cs_new:Npn \_\_metrix_break_node:n #1
332   {
333     \group_begin:
334       \cs_set:Npx \_\_metrix_current_highlight: {
335         \prop_item:NV \l_\_metrix_highlights_prop \l_\_metrix_process_int
336       }
337       \expandafter\tikzset\expandafter{\_\_metrix_current_highlight:}
338       \tikz[baseline=(l_\_metrix_break_node.base)]
339         \node (l_\_metrix_break_node) [every~metrix-break-node] { #1 }
340       ;
341     \group_end:
342   }
```

(End definition for `__metrix_break_node:n`)

`__metrix_e_gap:` This macro typsets the gap around the two break symbols.

```
347   \cs_new_protected:Npn \_\_metrix_e_gap:
348   {
349     \hskip*\usemetrixvar{emptywidth}
350   }
```

(End definition for `__metrix_e_gap:`)

`__metrix_evaluate_highlights:N` This macro evaluates and prints the highlighting options.

```
351   \cs_new_protected:Npn \_\_metrix_evaluate_highlights:n #1
352   {
```

Start with clearing the property list, otherwise the highlights from the last time will survive.

```
353   \prop_clear:N \l_\_metrix_highlights_prop
```

Then split and process the argument as a comma separated list.

```
354   \clist_map_inline:nn { #1 }
```

The result is a sequence of key value pairs that we store in `\l__metrix_highlight_seq`. The first part of this sequence must be split again at the plus sign—store it in `\l__metrix_highlight_pos_seq`.

```
356   \seq_set_split:Nnn \l_\_metrix_highlight_seq { = } { ##1 }
357   \seq_set_split:Nnf \l_\_metrix_highlight_pos_seq { + }
358   {
359     \seq_item:Nn \l_\_metrix_highlight_seq { 1 }
360   }
```

Process the `\l__metrix_highlight_pos_seq` list and set up the property list:

```
361     \seq_map_inline:Nn \l__metrix_highlight_pos_seq
362     {
363         \prop_put:Nnx \l__metrix_highlights_prop
```

The key is the current item of `\l__metrix_highlight_pos_seq`.

```
364     {
365         #####1
366     }
367 }
```

The value is the second item of `\l__metrix_highlight_seq`.

```
368     \seq_item:Nn \l__metrix_highlight_seq { 2 }
369 }
370 }
371 }
372 }
```

(End definition for `_metrix_evaluate_highlights:N`.)

9.6 Patching font macros

To apply the italic correction of the accents we need to patch the font switches.

```
373 \xpretocmd { \itshape }
374 {
375     \tl_set_eq:NN
376     \l__metrix_internal_itcorrection_tl
377     \g__metrix_variable_itcorrection_tl
378 }
379 { }
380 {
381     \_metrix_warning_msg:n { Could-not~patch~\string\itshape. }
382 }
383 \xpretocmd { \slshape }
384 {
385     \tl_set_eq:NN
386     \l__metrix_internal_itcorrection_tl
387     \g__metrix_variable_itcorrection_tl
388 }
389 { }
390 {
391     \_metrix_warning_msg:n { Could-not~patch~\string\slshape. }
392 }
393 \xpretocmd { \upshape }
394 {
395     \tl_set_eq:NN
396     \l__metrix_internal_itcorrection_tl
397     \g__metrix_internal_itcorrection_zero_tl
398 }
399 { }
```

```

400  {
401    \__metrix_warning_msg:n { Could-not~patch~\string\upshape. }
402  }
403 \xpretocmd { \normalfont }
404  {
405    \tl_set_eq:NN
406    \l__metrix_internal_itcorrection_tl
407    \g__metrix_internal_itcorrection_zero_tl
408  }
409  { }
410  {
411    \__metrix_warning_msg:n { Could-not~patch~\string\normalfont. }
412  }

```

9.7 Internal macros for metric symbols

__metrix_e_mark: The empty symbol.

```

413 \cs_new:Npn \__metrix_e_mark: { \__metrix_e_gap: }
(End definition for \__metrix_e_mark::)

```

__metrix_u_mark: The brevis symbol \cdot .

```

414 \cs_new:Npn \__metrix_u_mark:
415  {
416    \begin{tikzpicture}[every-metrix-symbol]
417      \draw (0,0) arc [start-angle=0, end-angle=180, radius=-0.225];
418    \end{tikzpicture}
419  }

```

(End definition for __metrix_u_mark::)

__metrix_--mark: The longa symbol -- .

```

420 \cs_new:Npn \__metrix_--mark:
421  {
422    \bool_if:NTF \l__metrix_short_syllable_bool
423    {
424      \begin{tikzpicture}[every-metrix-symbol]
425        \draw (0,0) -- ++(0.4,0);
426      \end{tikzpicture}
427    }
428    {
429      \begin{tikzpicture}[every-metrix-symbol]
430        \draw (0,0) --- ++(0.75,0);
431      \end{tikzpicture}
432    }
433  }

```

(End definition for __metrix_--mark::)

__metrix_uu_mark: The biceps symbol \asymp .

```
434 \cs_new:Npn \_\_metrix_uu_mark:
435 {
436   \begin{tikzpicture}[every-metrix-symbol]
437     \draw (0,0) arc [start-angle=0, end-angle=180, radius=-0.2];
438     \draw ($(0.4,0)+(\pgflinewidth,0)+(\usemetrixvar{gap},0)$) arc
439       [start-angle=0, end-angle=180, radius=-0.2];
440   \end{tikzpicture}
441 }
```

(End definition for __metrix_uu_mark::)

__metrix_uu_mark: The biceps symbol \asymp .

```
442 \cs_new:Npn \_\_metrix_uu__mark:
443 {
444   \begin{tikzpicture}[every-metrix-symbol]
445     \draw (0,0) arc [start-angle=0, end-angle=180, radius=-0.2];
446     \draw ($(0.4,0)+(\pgflinewidth,0)+(\usemetrixvar{gap},0)$) arc
447       [start-angle=0, end-angle=180, radius=-0.2];
448     \draw ($(0,-0.2)+(-0.5\pgflinewidth,-\pgflinewidth)-(0,\usemetrixvar{gap})$) --
449       ($(0.8,-0.2)+(1.5\pgflinewidth,-\pgflinewidth)
450       +(\usemetrixvar{gap},-\usemetrixvar{gap})$);
451   \end{tikzpicture}
452 }
```

(End definition for __metrix_uu__mark::)

__metrix_uu_mark: Another biceps symbol \bowtie .

```
453 \cs_new:Npn \_\_metrix_uu_mark:
454 {
455   \begin{tikzpicture}[every-metrix-symbol]
456     \draw (0,0) arc [start-angle=0, end-angle=180, radius=-0.2];
457     \draw ($(0.4,0)+(\pgflinewidth,0)+(\usemetrixvar{gap},0)$) arc
458       [start-angle=0, end-angle=180, radius=-0.2];
459     \draw ($(0,0)+(-0.5\pgflinewidth,0.5\pgflinewidth)+(0,\usemetrixvar{gap})$) --
460       ($(0.8,0)+(1.5\pgflinewidth,0.5\pgflinewidth)
461       +(\usemetrixvar{gap},\usemetrixvar{gap})$);
462   \end{tikzpicture}
463 }
```

(End definition for __metrix_uu_mark::)

__metrix_u_uu_mark: An another biceps symbol \bowtie .

```
464 \cs_new:Npn \_\_metrix_u_uu_mark:
465 {
466   \begin{tikzpicture}[every-metrix-symbol]
467     \draw (0,0) arc [start-angle=0, end-angle=180, radius=-0.2];
468     \draw ($(0.4,0)+(\pgflinewidth,0)+(\usemetrixvar{gap},0)$) arc
469       [start-angle=0, end-angle=180, radius=-0.2];
470     \draw ($(0,0)+(-0.5\pgflinewidth,0.5\pgflinewidth)+(0,\usemetrixvar{gap})$) --
```

```

471      ($ (0.8,0)+(1.5\pgflinewidth,0.5\pgflinewidth)
472      +(\usemetrixvar{gap},\usemetrixvar{gap})$);
473      \draw ($ (0.2,0.2)+(0.5\pgflinewidth,1.5\pgflinewidth)
474      +(0.5*\usemetrixvar{gap},2*\usemetrixvar{gap})$)
475      arc [start-angle=0, end-angle=180, radius=-0.2];
476      \end{tikzpicture}
477  }

```

(End definition for `__metrix_uu_mark`.)

`__metrix_x_mark`: The aneps symbol \times .

```

478 \cs_new:Npn \_\_metrix_x_mark:
479 {
480   \begin{tikzpicture}[every-metrix-symbol]
481     \draw (-0.2,0.2) -- (0.2,-0.2);
482     \draw (-0.2,-0.2) -- (0.2,0.2);
483   \end{tikzpicture}
484 }

```

(End definition for `__metrix_x_mark`.)

`__metrix_oo_mark`: The aeolic symbol $\circ\circ$.

```

485 \cs_new:Npn \_\_metrix_oo_mark:
486 {
487   \begin{tikzpicture}[every-metrix-symbol]
488     \draw (0,0) circle [radius=0.2];
489     \draw ($ (0.4,0)+(1\pgflinewidth,0)+(\usemetrixvar{gap},0)$) circle [radius=0.2];
490   \end{tikzpicture}
491 }

```

(End definition for `__metrix_oo_mark`.)

`__metrix_u_u_mark`: The indifferent symbol \backsimeq .

```

492 \cs_new:Npn \_\_metrix_u_u_mark:
493 {
494   \begin{tikzpicture}[every-metrix-symbol]
495     \draw (0,0) arc [start-angle=0, end-angle=180, radius=-0.2];
496     \draw ($ (0,-0.2)+(-0.5\pgflinewidth,-\pgflinewidth)-(0,\usemetrixvar{gap})$) --
497       ($ (0.4,-0.2)+(0.5\pgflinewidth,-\pgflinewidth)
498       +(0,-\usemetrixvar{gap})$);
499   \end{tikzpicture}
500 }

```

(End definition for `__metrix_u_u_mark`.)

`__metrix_n_mark`: An alternative indifferent symbol \curvearrowright .

```

501 \cs_new:Npn \_\_metrix_n_mark:
502 {
503   \begin{tikzpicture}[every-metrix-symbol]
504     \draw (0,0) arc [start-angle=0, end-angle=180, radius=0.225];
505     \fill (-0.225,0.75*\usemetrixvar{symbollinewidth})

```

```

506     circle [radius=0.7\pgflinewidth];
507   \end{tikzpicture}
508 }

```

(End definition for __metrix_n_mark:.)

__metrix_l_mark: The simple break symbol | (above syllables).

```

509 \cs_new:Npn \_\_metrix_l_mark:
510 {
511   \begin{tikzpicture}[every-metrix-symbol]
512     \draw (0,0) -- (0,0.5);
513   \end{tikzpicture}
514 }

```

(End definition for __metrix_l_mark:.)

__metrix_ll_mark: The verse break symbol || (above syllables).

```

515 \cs_new:Npn \_\_metrix_ll_mark:
516 {
517   \begin{tikzpicture}[every-metrix-symbol]
518     \draw (0,0) -- (0,0.5);
519     \draw ($(\pgflinewidth,0)+(1.5*\usemetrixvar{gap},0)$) -- ++(0,0.5);
520   \end{tikzpicture}
521 }

```

(End definition for __metrix_ll_mark:.)

__metrix_l_bigmark: The simple break symbol | (stand alone version).

```

522 \cs_new:Npn \_\_metrix_l_bigmark:
523 {
524   \begin{tikzpicture}[every-metrix-symbol]
525     \draw (0,0) -- (0,0.8);
526   \end{tikzpicture}
527 }

```

(End definition for __metrix_l_bigmark:.)

__metrix_ll_bigmark: The verse break symbol || (stand alone version).

```

528 \cs_new:Npn \_\_metrix_ll_bigmark:
529 {
530   \begin{tikzpicture}[every-metrix-symbol]
531     \draw (0,0) -- (0,0.8);
532     \draw ($(\pgflinewidth,0)+(1.5*\usemetrixvar{gap},0)$) -- ++(0,0.8);
533   \end{tikzpicture}
534 }

```

(End definition for __metrix_ll_bigmark:.)

`__metrix_l_break` The simple break symbol `|` (between syllables with symbols).

```

535 \cs_new:Npn \_\_metrix_l_break:
536 {
537   \begin{tikzpicture}[every metrix symbol, baseline=0.05em]
538     \draw (0,\usemetrixvar{symbolshift}+0.325em)
539       -- (0,-0.05em) -- (0,0.8em) -- (0,\usemetrixvar{symbolshift});
540   \end{tikzpicture}
541 }
```

(End definition for `__metrix_l_break`.)

`__metrix_ll_break` The verse break symbol `||` (between syllables with symbols).

```

542 \cs_new:Npn \_\_metrix_ll_break:
543 {
544   \begin{tikzpicture}[every metrix symbol, baseline=0.05em]
545     \draw (0,\usemetrixvar{symbolshift}+0.325em)
546       -- (0,-0.05em) -- (0,0.8em) -- (0,\usemetrixvar{symbolshift});
547     \draw
548     [
549       shift={($(\pgflinewidth,0)+(1.5*\usemetrixvar{gap},0)$)},
550     ]
551     (0,\usemetrixvar{symbolshift}+0.325em) -- (0,-0.05em) -- (0,0.8em)
552     -- (0,\usemetrixvar{symbolshift});
553   \end{tikzpicture}
554 }
```

(End definition for `__metrix_ll_break`.)

`__metrix_short_break:` The shorter break symbol.

```

555 \cs_new:Npn \_\_metrix_short_break:
556 {
557   \begin{tikzpicture}[every metrix symbol]
558     \draw (0,0.3) -- (0,-0.3);
559   \end{tikzpicture}
560 }
```

(End definition for `__metrix_short_break`.)

`__metrix_foot_break:` The shorter break symbol for foot breakt is the same as the regular short break.

```

561 \cs_set_eq:NN \_\_metrix_foot_break: \_\_metrix_short_break:
```

(End definition for `__metrix_foot_break`.)

9.8 User level macros

\setmetrixvar This macro saves the value to an internal variable.

```

562 \NewDocumentCommand{ \setmetrixvar }{ m m }
563 {
564   \tl_if_exist:cTF { g__metrix_variable_#1_tl } {
565     \tl_set:cn { g__metrix_variable_#1_tl } { #2 }
566   }
567   {
568     \__metrix_error_msg:n { Unknown~variable~'#1'. }
569   }
570 }
```

(End definition for `\setmetrixvar`. This function is documented on page 15.)

\usemetrixvar With this command one can access the value of an internal variable.⁴

```

571 \DeclareExpandableDocumentCommand{ \usemetrixvar }{ m }
572 {
573   \tl_if_exist:cTF { g__metrix_variable_#1_tl } {
574     \tl_use:c { g__metrix_variable_#1_tl }
575   }
576   {
577     \__metrix_error_msg:n { Unknown~variable~'#1'. }
578   }
579 }
```

(End definition for `\usemetrixvar`. This function is documented on page 15.)

\metrics This user macro calls `\@_metrics` to typeset syllables with symbols.

```

580 \NewDocumentCommand{ \metrics }{ O{} m m }
581 {
582   \__metrix_evaluate_highlights:n { #1 }
583   \__metrix_metrics:nn { #2 } { #3 }
584 }
```

(End definition for `\metrics`. This function is documented on page 4.)

\metricsymbols This command typesets stand alone symbols. The starred version prints smaller versions.

```

585 \NewDocumentCommand{ \metricsymbols }{ s O{} m }
586 {
587   \group_begin:
588   \IfBooleanF { #1 } { \tikzset{every-metrix-symbol/.style={every-metrix-big-symbol}} }
589   \__metrix_evaluate_highlights:n { #2 }
590   \__metrix_metricsymbols:n { #3 }
591   \group_end:
592 }
```

(End definition for `\metricsymbols`. This function is documented on page 2.)

⁴Marco Daniel showed me this hint at <http://tex.stackexchange.com/q/124600/4918>.

\lng This macro prints the longa accent above its argument.

```
593 \NewDocumentCommand { \lng } { D(){0,0} m 0{0pt} }
```

```
594 {
595   \begin{tikzpicture}[  
596     baseline = (l__metrix_syllable_node_\int_use:N \l__metrix_process_int.base),  
597     every-metrix-accent  
598   ]  
599   \node [every-metrix-syllable-node]  
600     (l__metrix_syllable_node_\int_use:N \l__metrix_process_int)  
601     { #3 };  
602   \begin{pgfinterruptboundingbox}  
603     \draw [shorten-< = -#2, shorten-> = -#4]  
604       ($ (l__metrix_syllable_node_\int_use:N \l__metrix_process_int.north)  
605       - (\usemetrixvar{lngminlength}/2,0)  
606       +(\usemetrixvar{accentxshift},\usemetrixvar{lngshift})  
607       + (\tl_use:N \l__metrix_internal_itcorrection_tl,0)  
608       + (#1)$)  
609     --  
610       ($ (l__metrix_syllable_node_\int_use:N \l__metrix_process_int.north)  
611       + (\usemetrixvar{lngminlength}/2,0)  
612       +(\usemetrixvar{accentxshift},\usemetrixvar{lngshift})  
613       + (\tl_use:N \l__metrix_internal_itcorrection_tl,0)  
614       + (#1)$)  
615     ;  
616     \draw [shorten-< = -#2, shorten-> = -#4]  
617       ($ (l__metrix_syllable_node_\int_use:N \l__metrix_process_int.north-west)  
618       +(\usemetrixvar{lngshortening}+\usemetrixvar{accentxshift},\usemetrixvar{lngshift})  
619       + (\tl_use:N \l__metrix_internal_itcorrection_tl,0)  
620       + (#1)$)  
621     --  
622       ($ (l__metrix_syllable_node_\int_use:N \l__metrix_process_int.north-east)  
623       +(-\usemetrixvar{lngshortening}+\usemetrixvar{accentxshift},\usemetrixvar{lngshift})  
624       + (\tl_use:N \l__metrix_internal_itcorrection_tl,0)  
625       + (#1)$)  
626     ;  
627   \end{pgfinterruptboundingbox}  
628 \end{tikzpicture}%  
629 }
```

(End definition for \lng. This function is documented on page 8.)

\brv This macro prints the brevis accent above its argument.

```
630 \NewDocumentCommand { \brv } { D(){0,0} m }
```

```
631 {
632   \begin{tikzpicture}[  
633     baseline = (l__metrix_syllable_node_\int_use:N \l__metrix_process_int.base),  
634     every-metrix-accent  
635   ]  
636   \node [every-metrix-syllable-node]  
637     (l__metrix_syllable_node_\int_use:N \l__metrix_process_int)
```

```

638     { #2 };
639     \begin{pgfinterruptboundingbox}
640       \draw ($(\l_metrix_syllable_node_\int_use:N \l_metrix_process_int.north)
641         + (-0.15,0)
642         + (\usemetrixvar{accentxshift},\usemetrixvar{brvshift})
643         + (\tl_use:N \l_metrix_internal_itcorrection_tl,0)
644         + (#1$)
645       arc [start-angle=0, end-angle=180, radius=-0.15];
646     \end{pgfinterruptboundingbox}
647   \end{tikzpicture}
648 }

```

(End definition for `\brv`. This function is documented on page 8.)

\acct This macro prints the dot accent below its argument.

```

649 \NewDocumentCommand { \acct } { D(){0,0} m }
650 {
651   \begin{tikzpicture}[%
652     baseline = (\l_metrix_syllable_node_\int_use:N \l_metrix_process_int.base),
653     every~metrix~accent
654   ]
655   \node [every~metrix~syllable~node]
656     (\l_metrix_syllable_node_\int_use:N \l_metrix_process_int)
657     { #2 };
658   \begin{pgfinterruptboundingbox}
659     \fill ($(\l_metrix_syllable_node_\int_use:N \l_metrix_process_int.south)
660       + (0,\usemetrixvar{dotshift})
661       + (#1$)
662       circle [radius=1.25\pgflinewidth];
663     \end{pgfinterruptboundingbox}
664   \end{tikzpicture}
665 }

```

(End definition for `\acct`. This function is documented on page 8.)

\bow This macro prints the bow below it's argument.

```

666 \NewDocumentCommand { \bow } { O{0pt} m O{0pt} }
667 {
668   \begin{tikzpicture}[%
669     baseline = (\l_metrix_syllable_node_\int_use:N \l_metrix_process_int.base),
670     every~metrix~bow
671   ]
672   \node [every~metrix~syllable~node]
673     (\l_metrix_syllable_node_\int_use:N \l_metrix_process_int)
674     { #2 };
675   \draw [shorten-< = #1, shorten-> = #3]
676     ($(\l_metrix_syllable_node_\int_use:N \l_metrix_process_int.base~west) +
677     (\usemetrixvar{bowshortening},\usemetrixvar{bowshift})$)
678     to [out=-45, in=225, looseness=\usemetrixvar{bowlooseness}]
679     ($(\l_metrix_syllable_node_\int_use:N \l_metrix_process_int.base~east) +

```

```

680      (-\usemetrixvar{bowshortening},\usemetrixvar{bowshift}));  

681  \end{tikzpicture}  

682 }

```

(End definition for `\bow`. This function is documented on page 9.)

9.9 TikZ styles

The `m̄etrix` package uses several TikZ sytles to draw the macros.

```

683 \ExplSyntaxOff  

684 \tikzset {  

685   every metrix symbol/.style={  

686     line width=\usemetrixvar{symbollinewidth},  

687     color=\usemetrixvar{symbolcolor},  

688     x=\usemetrixvar{baseunit},y=\usemetrixvar{baseunit},  

689   },  

690   every metrix big symbol/.style={  

691     line width=\usemetrixvar{bigsymbollinewidth},  

692     color=\usemetrixvar{symbolcolor},  

693     x=\usemetrixvar{bigbaseunit},y=\usemetrixvar{bigbaseunit},  

694   },  

695   every metrix symbol node/.style={  

696     inner sep=0pt, anchor=center,  

697   },  

698   every metrix break node/.style={  

699     inner sep=0pt, anchor=base,  

700   },  

701   every metrix syllable node/.style={  

702     inner sep=0pt, anchor=base,  

703   },  

704   every metrix bow/.style={  

705     line width=\usemetrixvar{bowlinewidth},  

706     color=\usemetrixvar{bowcolor},  

707     x=\usemetrixvar{baseunit},y=\usemetrixvar{baseunit},  

708   },  

709   every metrix accent/.style={  

710     line width=\usemetrixvar{accentlinewidth},  

711     color=\usemetrixvar{accentcolor},  

712     x=\usemetrixvar{baseunit},y=\usemetrixvar{baseunit},  

713   },  

714   bold highlight/.style={  

715     every metrix symbol/.append style={line width=2\pgflinewidth},  

716     every metrix syllable node/.append style={font=\bfseries},  

717     every superscript node/.append style={font/.expand once=\tikz@textfont\bfseries},  

718   },  

719   colored highlight/.style={  

720     every metrix symbol/.append style={draw=#1},  

721     every metrix syllable node/.append style={text=#1},  

722     every superscript node/.append style={text:#1},  

723   },

```

```

724 colored highlight/.default={  

725   \usemetrixvar{highlightcolor}  

726 },  

727 dashed highlight/.style={  

728   every metrix symbol/.append style={dash pattern=on 1pt off 0.4pt},  

729 },  

730 filled highlight/.style={  

731   every metrix symbol node/.append style={inner sep=2pt,fill=#1},  

732 },  

733 filled highlight/.default={  

734   \usemetrixvar{fillcolor},  

735 },  

736 every superscript picture/.style={  

737   baseline=-3ex,  

738 },  

739 every superscript node/.style={  

740   inner sep=0pt,  

741   font=\scriptsize,  

742 },  

743 every superscript label/.style={  

744   inner xsep=0pt,  

745   inner ysep=-3ex,  

746   label distance=0.5pt,  

747 },  

748 add superscript/.style={  

749   label={[every superscript label]right:{%  

750     \tikz[every superscript picture]\node at (0,0) [every superscript node] {#1};%  

751   }},  

752 },  

753 superscript/.style={  

754   every metrix symbol node/.append style={  

755     add superscript=#1,  

756   },  

757   every metrix break node/.append style={  

758     add superscript=#1,  

759   },  

760 },  

761 superscript/.value required,  

762 add arrow/.style={  

763   every metrix symbol node/.append style={  

764     label=90:\usemetrixvar{arrow},  

765   },  

766 },  

767 add text/.style={  

768   every metrix symbol node/.append style={  

769     label={[every metrix added text]#1},  

770   },  

771 },  

772 every metrix added text/.style = {  

773   font = \scriptsize\itshape,

```

```

774 },
775 add text/.value required,
776 }
777 \ExplSyntaxOn

```

9.10 Environments

symbolline Environment to display stand alone symbols.

```

778 \NewDocumentEnvironment{symbolline} { }
779 {
780   \par\addvspace{\baselineskip}
781   \centering
782 }
783 {
784   \par\vspace{\baselineskip}
785   \noindent\ignorespacesafterend
786 }

```

(End definition for *symbolline*. This function is documented on page 9.)

__metrix_print_vers_ref:n The internal macro to print the verse reference inside of {metricvers}

```

787 \cs_new:Npn \_\_metrix_print_vers_ref:n #1
788 {
789   \hspace*{\fill}\nolinebreak[1] \quad \hspace*{\fill} \mbox{\footnotesize #1}
790 }

```

(End definition for *__metrix_print_vers_ref:n*.)

metricverses Environment to display a verse with metric symbols and a source. And a macro to print a right aligned reference.

```

791 \NewDocumentCommand { \verseref } { m }
792 {
793   \_\_metrix_error_msg:n {
794     \string\verseref\space can~only~be~used~in~{metricverses}~env.
795   }
796 }
797 \NewDocumentEnvironment{metricverses} { }
798 {
799   \RenewDocumentCommand { \verseref } { m }
800   {
801     \_\_metrix_print_vers_ref:n { ##1 }
802   }
803   \par
804   \addvspace{0.7\baselineskip}
805   \fp_compare:nT { \usemetrixvar{symbolshift} < 0.0 }
806   {
807     \vspace{\usemetrixvar{symbolshift}}
808   }
809   \addtolength{\baselineskip}{0.6\baselineskip}

```

```

810   }
811   {
812     \par
813     \addtolength{\baselineskip}{-0.6\baselineskip}
814     \vspace{\baselineskip}
815     \noindent\ignorespacesafterend
816   }

```

(End definition for `metricverses` and `\verseref`. These functions are documented on page 10.)

817 </package>

10 Change History

| | | | | |
|-------|---|-----------|--|-----------|
| v1.0 | General: Initial version | <i>43</i> | case:nnF. | <i>25</i> |
| v1.0a | General: Added cwl file for TeXstudio . | <i>1</i> | __metrix_metricsymbols:n: Replaced deprecated \str_case:nnn with \str_case:nnF. | <i>26</i> |
| v1.1 | <ul style="list-style-type: none"> __metrix_l_break: Made line slightly longer __metrix_ll_break: Made lines slightly longer __metrix_metrics:nn: Made short breaks available __metrix_print_syllable:n: Symbol nodes get individual names now. __metrix_u_mark:: Removed red dot | <i>36</i> | General: New contact info (mail and URL). | <i>1</i> |
| v1.2 | <ul style="list-style-type: none"> \acct: Finetuning for \acct. \bow: Finetuning for \bow. \brv: Finetuning for \brv. \lng: Finetuning for \lng. | <i>39</i> | v1.2a | |
| | | | General: Replaced deprecated \prop_get variants (Thanks to J. Wright). | <i>43</i> |
| v1.3 | <ul style="list-style-type: none"> __metrix_metrics:nn: Extended short breaks feature \g_metrix_variable_arrow_tl: New variable for arrow | <i>23</i> | | |
| v1.1a | __metrix_metrics:nn: Replaced deprecated \str_case:nnn with \str_ | | | |

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

| A | B |
|------------------------|--|
| \acct | <i>8, 8, 8, 8, <u>39</u>, 39</i> |
| \addtolength | <i>42, 43</i> |
| \addvspace | <i>42, 42</i> |
| | \baselineskip |
| | <i>42, 42, 42, 42, 43, 43, 43</i> |
| | \begin |
| | <i>28, 28, 29, 32, 32, 32, 33, 33, 33, 33, 34, 34, 34, 34, 35, 35,</i> |

| | |
|-----------------------------------|---|
| \itshape | 31, 31, 41 |
| \bfseries | 40, 40 |
| \boldhighlight | 18 |
| \bow | 9, 9, 9, 9, 16, 17, 39, 39 |
| \brv | 8, 8, 8, 8, 16, 17, 18, <u>38</u> , 38 |
| C | |
| \centering | 42 |
| \coloredhighlight | 18 |
| \coordinate | 26 |
| D | |
| dashedhighlight | 18 |
| \DeclareExpandableDocumentCommand | 37 |
| \downarrow | 17, 22 |
| \draw | 32, 32, 32, 33, 33, 33, 33, 33, 33, 33, 33, 33, 33, 34, 34, 34, 34, 34, 34, 34, 35, 35, 35, 35, 35, 35, 36, 36, 36, 36, 38, 38, 39, 39, 39 |
| E | |
| \end | 28, 28, 29, 32, 32, 32, 33, 33, 33, 34, 34, 34, 34, 35, 35, 35, 35, 36, 36, 36, 38, 38, 39, 39, 39, 39, 40 |
| everymetrixaccent | 18 |
| everymetrixaddedtext | 18 |
| everymetrixbigsymbol | 18 |
| everymetrixbow | 18 |
| everymetrixbreaknode | 18 |
| everymetrixsyllablenode | 18 |
| everymetrixtsymbol | 18 |
| everymetrixtsymbolnode | 18 |
| everysuperscriptlabel | 18 |
| everysuperscriptnode | 18 |
| everysuperscriptpicture | 18 |
| \expandafter | 28, 28, 29, 29, 30, 30 |
| \ExplSyntaxOff | 19, 40 |
| \ExplSyntaxOn | 19, 42 |
| F | |
| \fill | 34, 39, 42, 42 |
| \filledhighlight | 18 |
| \footnotesize | 42 |
| H | |
| \hspace | 26, 29, 30, 42, 42 |
| I | |
| \IfBooleanF | 37 |
| \ignorespacesafterend | 42, 43 |
| L | |
| \ln | 8, 8, 8, 8, 16, 17, 18, <u>38</u> , 38 |
| M | |
| \mbox | 42 |
| \metrics | 2, 4, 4, 4, 4, 5, 12, 12, 13, 22, 22, 22, 22, 23, <u>37</u> , 37 |
| \metricsymbols | 2, 2, 4, 4, 5, 5, 13, 22, 22, 26, <u>37</u> , 37 |
| metricverses | 10, 42 |
| \metrixFileDate | 18 |
| \metrixFileDescription | 18 |
| \metrixFileName | 18, 29, 29 |
| \metrixFileVersion | 18 |
| N | |
| \NewDocumentCommand | 37, 37, 37, 38, 38, 39, 39, 42 |
| \NewDocumentEnvironment | 42, 42 |
| \node | 25, 26, 28, 28, 29, 30, 38, 38, 39, 39, 41 |
| \noindent | 42, 43 |
| \nolinebreak | 42 |
| \normalfont | 32, 32 |
| P | |
| \PackageError | 29 |
| \PackageWarning | 29 |
| \par | 42, 42, 42, 43 |
| \pgflinewidth | 33, 33, 33, 33, 33, 33, 33, 34, 34, 34, 34, 34, 34, 34, 34, 35, 35, 35, 36, 39, 40 |
| \ProvidesExplPackage | 18 |
| Q | |
| \quad | 42 |
| R | |
| \RenewDocumentCommand | 42 |
| \RequirePackage | 19, 19, 19 |
| S | |
| \scriptsize | 41, 41 |
| \setmetrixvar | 15, 15, 15, 19, <u>37</u> , 37 |
| \slshape | 31, 31 |
| \space | 42 |
| \string | 31, 31, 32, 32, 42 |
| superscript | 18 |
| symbolline | 9, 42 |

| | |
|---------------|---|
| T | |
| \tikz | 25, 26, 30, 41 |
| \tikzset | 28, 29, 30, 37, 40 |
| | |
| U | |
| \upshape | 31, 32 |
| \usematrixvar | 15, 15, 18, 19, 26, 28, 29, 29, 30, 33, 33, 33, 33, 33, 33, 33, 33, 33, 33, 34, 34, 34, 34, 34, 34, 34, 34, 35, 35, 36, 36, 36, 36, 36, 36, 36, 37, 37, 38, 38, 38, 38, 38, 38, 38, |
| | |
| V | |
| \verseref | 10, 10, 10, 10, 42, 42, 42, 42 |
| \vspace | 42, 42, 43 |
| | |
| X | |
| \xpretocmd | 31, 31, 31, 32 |